

Standard Guidelines for Product Review
TAPE, NON REFLECTIVE;
Section 00225.13
April 11, 2005

00225.13 – Tape, Non Reflective

ODOT maintains a list of products suitable for placement on concrete or asphalt surfaces to temporarily cover existing pavement markings.

Specifications - Acceptable Tape Must:

- Be available in widths of at least 6 to 8 inches.
- Be Removable.
- Be black in color, or a color that will blend into the surrounding surfacings.
- Adhere to asphalt or concrete,
- Adhere to commonly used markings like waterborne traffic paint, methyl methacrylate (MMA), thermoplastic and other tapes,
- Not include any retro reflective elements.
- Include anti-skid materials.
- Not wash out in sunlight, with headlights; or otherwise look like a pavement marking to traveling motorists (day or night).

Our requirements for non-reflective are that it should mask the existing marking during day and night without appearing as a stripe, for an extended period, and be easily removed without leaving any residue on the highway, or damaging the existing marking.

To apply for inclusion on the QPL, submit the following:

- Preliminary information for Product Evaluation Form.
- Spec data sheet.
- Documentation showing compliance with the above specifications.
- Detailed installation instructions.
- List of limitations and precautions.
- Submit samples for examination (4 each 10" samples)
- Other DOT approvals (with contact information).
- Copies of independent testing you have done.
- Copies of NTPEP testing you have done.

Submit documentation to:

Oregon DOT

Mike Dunning

800 Airport Road SE

Salem OR 97301-4798

<http://www.oregon.gov/ODOT/HWY/CONSTRUCTION/QPL/QPIIndex.shtml>