

SECTION 00866 - LONGITUDINAL PAVEMENT MARKINGS - HIGH PERFORMANCE

(Follow all instructions. If there are no instructions above a subsection, paragraph, sentence, or bullet, then include them in the project. The specifications may be modified to include project specific specifications, but all additions, deletions, or modifications must be sent to the ODOT Technical Resource and Senior Specifications Engineer for review and approval.)

Comply with Section 00866 of the Standard Specifications-modified as follows:

00866.45 Installation - In the paragraph that begins "Apply marking materials by one...", replace the bullet list with the following bullet list:

- Method 1: Extruded Markings - Apply markings with an extrusion or ribbon type process.
- Method 2: Sprayed Markings - If more than one application is required to obtain the specified thickness, retrace additional applications directly over previous applications within 1/16 inch.
- Method 1-2: Extruded or Sprayed Markings - Install Method 1 markings or Method 2 markings.

Add the following paragraph to the end of this subsection:

For grooved markings, grind the slot depth as shown. Apply the specified marking material so the slot is filled from edge to edge as shown. The top of the marking shall be flat or slightly convex.

00866.90 Payment - Replace this subsection, except for the subsection number and title, with the following:

The accepted quantities of work performed under this Section will be paid for at the Contract unit price, per unit of measurement, for the following items:

(Delete pay items that do not apply. When deleting all pay items under a pay item heading, also delete the heading.)

| <u>Pay Item</u> | <u>Unit of Measurement</u> |
|---|----------------------------|
| <u>Method 1 (Extruded)</u> | |
| <u>(a) Plural Component, Extruded,</u> | <u>Foot</u> |
| <u>(b) Plural Component, Extruded, Wet Weather,</u> | <u>Foot</u> |
| <u>(c) Hi-Build Paint, Extruded,</u> | <u>Foot</u> |
| <u>(d) Hi-Build Paint, Extruded, Wet Weather,</u> | <u>Foot</u> |
| <u>Method 2 (Sprayed)</u> | |

- (e) Plural Component, Sprayed, Foot
- (f) Plural Component, Sprayed, Wet Weather, Foot
- (g) Hi-Build Paint, Sprayed, Foot
- (h) Hi-Build Paint, Sprayed, Wet Weather, Foot

Method 1-2 (Extruded or Sprayed)

- (i) Plural Component, Extruded or Sprayed, Foot
- (j) Plural Component, Extruded or Sprayed, Wet Weather, Foot
- (k) Hi-Build Paint, Extruded or Sprayed, Foot
- (l) Hi-Build Paint, Extruded or Sprayed, Wet Weather, Foot

The word "Surface" or "Grooved" will be inserted in the blank.

Payment will be payment in full for furnishing and placing all materials, and or furnishing all equipment, labor, and incidentals necessary to complete the work as specified.

Payment for work under this Section will be limited to 75 percent of the amount due until the Agency has received the signed Warranty.